


SURFACE MOUNT CLOCK OSCILLATORS (Rohs Compliant / Lead Free)
Oscillators SMD3.2x2.5mm (APO-SMD03 Series) 2.5V

APX - Crystal


- SPECIFICATIONS

FREQUENCY RANGE		1.544MHz TO 9.999MHz	10MHz TO 34.999MHz	35MHz TO 49.999MHz	50MHz TO 80MHz
FREQUENCY STABILITY (ALL INCLUSIVE*)		±20PPM, ±25PPM, ±50PPM, ±100PPM			
TEMPERATURE RANGE	OPERATING	0℃ TO +70℃ STANDARD			
		-40℃ TO +85℃ EXTENDED			
	STORAGE	-55℃ TO +125℃			
AGING (FIRST YEAR)		±5PPM			
INPUT	VOLTAGE	+2.5VDC ±10%			
	CURRENT (MAX.)	7mA	8mA	20mA	30mA
OUTPUT	LOAD	HCMOS		15pF Max	
	SYMMETRY	NORMAL: 40% TO 60%			
		TIGHT: 45% TO 55%			
	VOLTAGE	VOH	90% VDD min		
		VOL	10% VDD max		
	RISE/FALL TIME	6nS Max (Tr: 10%VDD~90%VDD, Tf: 90%VDD~10%VDD)			
START-UP TIME		10mS max			
PIN 1, TRI-STATE FUNCTION		Pin 1=H or open... Output active at pin 3 Pin 1=L... high impedance at pin 3			



*Include: 25°C tolerance, operating temperature range, input voltage change, aging 1st year, load change, shock and vibration

- OUTLINE DIMENSIONS




Recommended Solder Pattern


PIN	CONNECTION
#1	Tri-State/NC
#2	GND
#3	Output
#4	+2.5VDC

Unit: mm

- SOLDER REFLOW PROFILE



- CARRIER TAPE DIMENSIONS (3,000 pcs/reel)



A	B	C	D	E	F
1.5±0.1	4.0±0.1	4.0±0.1	3.5±0.1	8.0±0.3	1.0±0.1

ORDERING CODE SYSTEM (VERSION 1.2 UPDATED MAY 2008)						EXAMPLE:
SERIES	STABILITY	FREQUENCY	INPUT VOLTAGE	TEMPERATURE RANGE	OPTIONAL / BLANK	APO-SMD03P-25-2.5XT
APO-SMD03	D: ±20PPM E: ±25PPM J: ±50PPM P: ±100PPM	IN MHZ	2.5	X: EXTENDED TEMPERATURE (-40 TO +85 °C)	T – TIGHT SYMMETRY OTHERS – SPECIAL BLANK – STANDARD	

NON STANDARD FREQUENCIES AND SPECIFICATIONS ARE AVAILABLE ON REQUEST

ActPro Ltd. (APX-Crystal)
PROREP
EDGE Meditronics PTE Ltd.

HONG KONG
FRANCE
SINGAPORE

Email: sales@apx-crystal.com
Email: sales@prorep.fr
Email: sales@edgemeditronics.com.sg

Internet: www.apx-crystal.com
Internet: www.prorep.fr
Internet: www.edgemeditronics.com.sg

Tel: 852-3625 2368 Fax: 852-2633 8503
Tel: 33-1-4812 1736 Fax: 33-1-4812 1739
Tel: 65-6455 0521 Fax: 65-6455 0857

Specifications are subject to change without notice